

FEATURES :

- Frequency range : 5-1000 MHz
- Zinc die cast housing
- Grounding terminal provided.
- Low insertion loss, high return loss



Model : TAP - 3871 , -8 dB, 1 WAY TAPOFF

	Frequency Range (MHz)			
	5~40	40~470	470~860	860~1000
Tap Loss (dB)	± 1	± 1	± 1	± 1.5
Insertion Loss (dB)	≤ 2.0	≤ 2.0	≤ 2.2	≤ 2.6
Directional Loss (dB)	≥ 25	≥ 25	≥ 24	≥ 22
Return Loss (dB)	≥ 18	≥ 18	≥ 17	≥ 17



Model : TAP - 3872 , -10 dB, 2 WAYS TAPOFF

	Frequency Range (MHz)			
	5~40	40~470	470~860	860~1000
Tap Loss (dB)	± 1	± 1	± 1.2	± 1.5
Insertion Loss (dB)	≤ 2.5	≤ 3.2	≤ 3.2	≤ 3.5
Directional Loss (dB)	≥ 24	≥ 22	≥ 22	≥ 21
Isolation (dB)	≥ 20	≥ 24	≥ 24	≥ 20
Return Loss (dB)	≥ 18	≥ 20	≥ 20	≥ 18



Model : TAP - 3874 , -12 dB, 4 WAYS TAPOFF

	Frequency Range (MHz)			
	5~40	40~470	470~860	860~1000
Tap Loss (dB)	± 1	± 1	± 1.2	± 1.5
Insertion Loss (dB)	≤ 2.5	≤ 3.2	≤ 3.2	≤ 3.5
Directional Loss (dB)	≥ 24	≥ 22	≥ 22	≥ 21
Isolation (dB)	≥ 20	≥ 24	≥ 24	≥ 20
Return Loss (dB)	≥ 18	≥ 20	≥ 20	≥ 18