LNBF C-BAND 4 OUTPUT , Brand : INFOSAT Model : M4

SPECIFICATIONS :

Model No.	M4
Input Frequency Range	3.4 - 4.2 GHz
Output 1 & 2 & 3 & 4 Frequency Range	950 - 1750 MHz
L.O. Frequency	5.150 GHz
Noise Figure	17 °K
Conversion Gain	65 dB (Typ.)
Gain Flatness	± 1 dB / 36 MHz
L.O. Frequency Stability	± 2 MHz
Switching Voltage	13V / 18V
L.O. Phase Noise (1 KHz)	- 50 dBc/Hz
(10 KHz)	- 75 dBc/Hz
(100 KHz)	- 95 dBc/Hz
Image Rejection	45 dB (MIN)
Output V.S.W.R	2 : 1
IF Output Connector	75 Ω F Type (Female)
RF Input Connector	Wave Guide WC-229
D.C. Supply Voltage	H: 15.5 ~ 25 V
	V: 10 ~ 13.5 V
Supply Current	250 mA (MAX)
Operating Temperature	-40°C ~ 70°C

_INFOSAT_CO., LTD.
46/22 Moo.5 Tiwanon Rd., Banmai., Pakkred., Nonthaburi 11120 Thailand Tel. (66) 2- 961-9161-3 Fax: (66) 2- 961-8587 E-mail: sales@infosats.com