

MINI OUTDOOR TAPS (5 - 750 MHz)



ODT-7272



ODT-7274

FEATURE

- ❑ 5 – 750 MHz
- ❑ WITH ALL “ F ” CONNECTORS
- ❑ WATER-PROOF
- ❑ POWER PASS : 6A

SPECIFICATIONS

SPEC	FREQ	MODEL						
		ODT - 7272 (-8 dB)	ODT - 7272 (-11dB)	ODT-7274 (-11dB)	ODT-7274 (-14dB)	ODT-7274 (-17dB)	ODT-7274 (-20dB)	ODT-7274 (-23dB)
POWER PASS	IN-OUT	PASS	PASS	PASS	PASS	PASS	PASS	PASS
	IN-TAP	NO	NO	NO	NO	NO	NO	NO
TAP LOSS	5-750 MHz	8 ± 1 dB	11 ± 1 dB	11 ± 1 dB	14 ± 1 dB	17 ± 1 dB	20 ± 1 dB	23 ± 1 dB
INSERTION LOSS	5 MHz	3.5 dB	1.6 dB	3.5 dB	2.5 dB	1.8 dB	1.2 dB	1.0 dB
	400 MHz	3.6 dB	1.7 dB	3.8 dB	2.7 dB	2.2 dB	1.5 dB	1.2 dB
	600 MHz	3.8 dB	2.0 dB	4.0 dB	2.8 dB	2.3 dB	1.8 dB	1.5 dB
	750 MHz	4.3 dB	2.3 dB	4.2 dB	3.3 dB	2.6 dB	2.0 dB	1.8 dB
RETURN LOSS								
IN OUT TAP	5-750 MHz	15 dB	16 dB	15 dB	15 dB	15 dB	15 dB	15 dB
	5-750 MHz	15 dB	15 dB	15 dB	16 dB	15 dB	16 dB	16 dB
	5-750 MHz	15 dB	15 dB	15 dB	16 dB	15 dB	16 dB	16 dB
ISOLATION OUT-TAP	5 MHz	20 dB	20 dB	20 dB	20 dB	20 dB	20 dB	20 dB
	400 MHz	25 dB	25 dB	26 dB	27 dB	27 dB	28 dB	28 dB
	600 MHz	24 dB	25 dB	25 dB	26 dB	26 dB	27 dB	27 dB
	750 MHz	23 dB	25 dB	25 dB	25 dB	25 dB	25 dB	25 dB
ISOLATION TAP-TAP	5 MHz	20 dB	20 dB	20 dB	20 dB	20 dB	20 dB	20 dB
	400 MHz	25 dB	25 dB	25 dB	25 dB	26 dB	26 dB	26 dB
	600 MHz	24 dB	24 dB	24 dB	25 dB	26 dB	27 dB	27 dB
	750 MHz	24 dB	23 dB	23 dB	24 dB	25 dB	26 dB	26 dB