



INFOSAT INTERTRADE CO.,LTD.
 ADD: 46/22 Moo.5 Tiwanon Rd., Banmai, Pakkred,
 Nonthaburi, Thailand
 TEL: +66-2-9619161 FAX: +66-2-9618587
 URL: www.infosats.com Email: niran@infosats.com

Q1160BV

1) Description

14 gauge (1.63mm) copper covered steel center conductor;
 gas expanded polyethylene dielectric; inner shield aluminum
 foil overlap bonded to dielectric; outer shield of bare aluminum
 braid wire; with messenger; jacket of PVC. Nominal O.D.10.16mm.

2) Physical Dimensions

Center Conductor:-----1.63±0.01mm Copper Clad Steel
 Dielectric:-----7.11±0.05mm Foam PE
 Shield:-----Bonded AL Foil 100%
 Braid Coverage:-----60% X16X6X0.16±0.005mm AL Wire
 Jacket:-----10.16±0.05mm PVC

3) Mechanical Characteristics

Operating Temperature Range:-----20°C To +75°C
 Max. Recommended Pulling Tension: ----97 lbs
 Min. Bend Radius (Install):-----4.5 in.

4) Electrical Characteristics

Sparker Test:-----4000VAC
 Impedance:-----75±3Ω
 Capacitance:-----54±3pF/m
 Velocity of Propagation:---85%
 SRL:-----23dB (5-450MHz)



5) Attenuation

Attenuation		[@68°F. (20°C)]	
Frequency (MHz)	Max. (dB/100 ft)	Frequency (MHz)	Max. (dB/100 ft)
5	0.38	500	2.90
55	0.96	550	3.04
83	1.18	600	3.18
100	1.50	750	3.65
187	1.75	865	3.98
211	1.90	1000	4.35
250	2.05	1500	6.91
300	2.25	2000	8.13
400	2.60	2500	9.20
450	2.75	3000	10.20

6) Printing:

INFOSAT Q1160BV, Premier Cable, 001 meter --- 305 meters